

select	Inquiry	Bearing number	Dimension mm														load rating kN		Weight kg	
			d	B	dk	C1 max	d2	G	h1	l3 min	l4	l5	W	d3	d4	rs min	a°	dynamic load		static load
	SIJ5	5	8	11.112	7	16	M5	27	12.5	35	4	10	9	12	0.3	7	2.3	5.9	0.016	
	SIJ6	6	9	12.7	7	18	M6	30	13.5	39	5	11	10	13	0.3	11	3.2	6.5	0.02	
	SIJ8	8	12	15.875	9	22	M8	36	16	47	5	14	12.5	16	0.3	14	5.3	8	0.037	
	SIJ10	10	14	19.05	11	26	M10	43	19.5	56	6.5	17	15	19	0.3	12	7.3	10.5	0.061	
	SIJ12	12	16	22.225	12	30	M12	50	24	65	6.5	19	17.5	22	0.3	13	8.5	13	0.089	
	SIJ14	14	19	25.4	14	34	M14	57	27	74	8	22	20	25	0.3	14	12	17	0.135	
	SIJ16	16	21	28.575	15	38	M16	64	33	83	8	22	22	27	0.3	15	16.5	21	0.171	
	SIJ18	18	23	31.75	17	42	M18x1.5	71	36	92	10	27	25	31	0.6	14	20	25.5	0.246	
	SIJ20	20	25	34.925	18	46	M20x1.5	77	40	100	10	30	27.5	34	0.6	14	23	30	0.314	
	SIJ22	22	28	38.1	20	50	M22X1.5	84	43	109	12	32	30	37	0.6	15	27.5	35.5	0.41	