

SABP...N,N/B1□N/B2

select	Inquiry	Bearing number	Dimension mm													load rating kN		Weight kg
			d	d ₃ 6g	B	C ₁	L ₁ min	d ₁	d ₂	h	L ₂	d _k	r ₁	a	dynamic load	static load		
SABP5N	5	M5x0.8	8	6	20	7.7	16	33	41	11.11	0.3	13	3.25	5.7	0.013			
SABP6N	6	M6x1.0	9	6.75	22	8.96	18	36	45	12.7	0.3	13	4.3	7.2	0.02			
SABP8N	8	M8x1.25	12	9	25	10.4	22	42	53	15.875	0.3	14	7.2	11.6	0.03			
SABP10N	10	M10x1.5	14	10.5	29	12.9	26	48	61	19.05	0.3	13	10	14.6	0.055			
SABP12N	12	M12x1.75	16	12	33	15.4	30	54	69	22.225	0.3	13	13.4	17	0.085			
SABP12N/B2	12	M12x1.25	16	12	33	15.4	30	54	69	22.225	0.3	13	13.4	17	0.085			
SABP14N	14	M14x2.0	19	13.5	36	16.9	34	60	77	25.4	0.3	16	17	24	0.14			
SABP16N	16	M16x2.0	21	15	40	19.4	40	66	86	28.575	0.3	15	21.6	28.5	0.21			
SABP16N/B1	16	M16x1.5	21	15	40	19.4	40	66	86	28.575	0.3	15	21.6	28.5	0.21			
SABP18N	18	M18x1.5	23	16.5	44	21.9	44	72	94	31.75	0.3	15	26	42.5	0.28			
SABP20N	20	M20x1.5	25	18	47	24.4	50	78	103	34.925	0.3	14	31.5	52.5	0.38			
SABP22N	22	M22x1.5	28	20	51	25.8	54	84	111	38.1	0.3	15	38	57	0.48			
SABP25N	25	M24x2.0	31	22	57	29.6	60	94	124	42.86	3	15	47.5	68	0.64			
SABP28N	28	M27x2.0	35	24	62	32.3	66	103	136	47.63	0.3	15	58	75.5	0.96			
SABP30N	30	M30x2.0	37	25	66	34.8	70	110	145	50.8	0.3	17	64	88	1.1			