

# SQZL..RS

select	Inquiry	Bearing number Bearing number	dimension mm															Static load ratings kN	Weight kg
			d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	l <sub>1</sub>	l <sub>2</sub>	S <sub>1</sub>	L	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	D <sub>1</sub>	D <sub>2</sub>	D <sub>3</sub>	S <sub>2</sub>	a°		
SQZ5-RS	M5	9	19	8	11	7	46	24	4	12	9	11	17	9	15	2.8	0.025		
SQZ6-RS	M6	10	20	11	12.2	8	55.2	28	5	15	10	13	20	11	15	3.7	0.041		
SQZ8-RS	M8	12	24	12	16	10	65	32	5	16	12.5	16	24	14	15	5.8	0.075		
SQZ10-RS	M10xl.25	14	30	15	19.5	11	74.5	35	6.5	18	15	19	28	17	15	8.4	0.12		
SQZ12-RS	M12xl.25	17	32	17	21	15	84	40	6.5	20	17.5	22	32	19	15	11	0.18		
SQZ14-RS	M14xl.5	19	38	22	23.5	17	103	45	8	25	20	25	36	22	11	15	0.27		
SQZ16-RS	M16xl.5	22	44	23	25.5	19	112	50	8	27	22	27	40	22	11	15	0.36		
SQZ18-RS	M18xl.5	23	45	25	31	20	130.5	58	10	32	25	31	45	27	11	19	0.54		
SQZ20-RS	M20xl.5	27	50	25	29	24	133	63	10	38	27.5	34	45	30	7.5	19	0.57		
SQZ22-RS	M22xl.5	27	52	26	33	24	145	70	12	43	30	37	50	32	7.5	23	0.76		