

CF series bimetallic composite bearing

select Inquiry	d	D	轴径	座孔	壁厚	Go	No.Go	C ₁	C ₂	H 0							
			Shaft Dia	Housing bore	Wall thickness					-0.40							
				H7						10	15	20	25	30	40	50	60
10	12	10 -0.016 -0.034	12 +0.018	1 -0.025	12.075	12.035	0.5	0.3	1010	1015	1020						
12	14	12 -0.016 -0.034	14 +0.018	1 -0.025	14.075	14.035	0.5	0.3	1210	1215	1220						
13	15	13 -0.016 -0.034	15 +0.018	1 -0.025	15.075	15.035	0.5	0.3	1310	1315	1320						
14	16	14-0.016 -0.034	16 +0.018	1 -0.025	16.075	16.035	0.5	0.3	1410	1415	1420						
15	17	15-0.016 -0.034	17 +0.018	1 -0.025	17.075	17.035	0.5	0.3	1510	14515	1520						
16	18	16-0.016 -0.034	18 +0.018	1 -0.025	18.075	18.035	0.8	0.4	1610	1615	1620						
17	19	17-0.016 -0.034	19 +0.021	1 -0.025	19.085	19.040	0.8	0.4	1710	1715	1720						
18	20	18 -0.016 -0.034	20 +0.021	1 -0.025	20.085	20.040	0.8	0.4	1810	1815	1820	1825					
20	23	20-0.020 -0.041	23 +0.021	1.5 -0.025	23.085	23.040	0.8	0.4	2010	2015	2020	2025					
22	25	22 -0.020 -0.041	25 +0.021	1.5 -0.025	25.085	25.04	0.8	0.4	2210	2215	2220	2225					
24	27	24 -0.020 -0.041	27 +0.021	1.5 -0.025	27.085	28.040	1.0	0.5	2410	2415	2420	2425	2430				
25	28	25 -0.020 -0.041	28 +0.021	1.5 -0.025	28.085	28.040	1.0	0.5		2515	2520	2525	2530				
26	30	26 -0.020 -0.041	30 +0.021	2 -0.025	30.105	30.060	1.0	0.5		2615	2620	2625	2630				
28	32	28 -0.020 -0.041	32 +0.025	2 -0.025	32.105	32.060	1.0	0.5		2815	2820	2825	2830	2840			
30	34	30-0.020 -0.041	34 +0.025	2 -0.025	34.105	34.060	1.2	0.6		3015	3020	3025	3030	3040			
32	36	32 -0.025 -0.050	36 +0.025	2 -0.025	36.105	36.060	1.2	0.6		3215	3220	3225	3230	3240			
35	39	35-0.025 -0.050	39 +0.025	2 -0.025	39.105	39.060	1.2	0.6		3515	3520	3525	3530	3540	3550		
38	42	38-0.025 -0.050	42 +0.025	2 -0.025	42.105	42.060	1.2	0.6			3820	3825	3830	3840	3850		
40	44	40 -0.025 -0.050	44 +0.025	2 -0.025	44.105	44.060	1.2	0.6			4020	4025	4030	4040	4050		